



Excellent Design & Manufacture

## Pressure and Vacuum Detectors for Process Applications

### EDM pressure detectors

are rugged, field-mounted instruments. The pressure sensing element of the EDM pressure detector is a force-balance, piston-actuated assembly. The sensing element is sealed by a flexible diaphragm and a static o-ring. A wide selection of wetted parts materials for media compatibility and containment are available. A metal diaphragm may be welded to the pressure port for certain applications, thereby eliminating the o-ring.

### Application Information

The EDM pressure detectors in this catalog are suitable for a variety of process applications. Basic models with standard wetted parts are normally suitable for air, oil, water and non-corrosive processes. Certain applications may require customized specials. Consult the EDM representative in your area or the factory.



#### Features and Benefits

##### Complete Product Line

- Standard models and customized specials cover pressure ranges from 30 inches Hg VAC to 4000 psi.

##### Robust Construction

- Rugged, high-cycle rate tolerance, long life, not critical to vibration, high overrange and proof pressures, excellent corrosion resistance to hostile environments.
- Enclosure ratings: NEMA 1, 4, 4X, 7, or 9 available.
- Ingress protection rating up to IP66.

##### Instrument Quality

- High resolution of set points, high repeatability, narrow dead band, negligible temperature effect.

##### Wetted Parts

- Wide selection materials, process connection configurations and sizes. Optional "fire-safe" pressure sensor.

##### Snap-Action Electrical Detecting

- Wide selection UL Listed and CSA Certified detecting elements for AC and DC service. Optional "hermetically sealed" capsule for hazardous and hostile environments.

##### Field Adjustable

- Self-locking adjustment, no special tools required. No-charge factory calibration.

##### Cost Effective

- Simple and fast installation without special tools, long service life, no required periodic service or spare parts.

##### Agency Listings/Certification

- Select models with ATEX, IECEx, CSA, FM, GOST R, INMETRO, Rostekhnadzor (RTN), TIIS, UL
- Meets most code and customer requirements.

##### Safety Certified to IEC 61508 (SIL)

- EDM products are certified to IEC 61508 for non-redundant use in SIL1 and SIL2 Safety Instrumented Systems for most models. For more details or values applicable to a specific product, see the Safety Integrity Level Quick Guide.

##### Shock/Vibration

- Select models tested to MIL-S-901D (Navy) shock test.
- Select models tested to MIL-S-167 vibration test.

##### Built-In Quality

- Rigid quality standards maintained from raw material to finished product.

##### Delivery

- Routine shipments 7 to 10 working days. Emergency shipments via same day air.

##### Service

- Factory sales engineers and area EDM representatives provide effective and prompt worldwide service.

## Model Number System

# EEE601-509031-509

Adjustable Range		Typical Dead Band		Overrange		Proof	
psi	bar	psi	mbar	psi	bar	psi	bar
2 to 25	0.14 to 1.7	0.3	20.7	750	50	1000	70

## Product Specifications

### Housing

Weatherproof NEMA 4, 4X, IP66

Six-place compression type terminal block

Electrical 3/4" NPT(F) - Right

Material Copper-free aluminum

### Detecting Element

Designator DPDT

Rating 5 Amps @ 30 VDC

Dead Band Multiplier 4.0

### Wetted Materials

Diaphragm TCP Teflon-Coated Polyimide

O-Ring Buna-N

### Pressure Port

Process Connection Size 1/4" NPT(F)

Pressure Port Material Aluminum

## Weatherproof - NEMA 4, 4X, IP66

